



Model SRF612

Wireless Temperature Transmitter

The SRF612 is used for wireless temperature measurement inside applications like refrigerators, freezers, and incubators. Up to four (4) external temperature sensor probes and a door contact sensor can be connected to one SRF612 Wireless Temperature Transmitter.

Probes and accessories are purchased separately. Please refer to Setra's website or the SRF600 Wireless Probes and Accessories Data Sheet.

If you wish to connect 2, 3 or 4 sensor probes to the SRF612 Wireless Temperature Transmitter, you need to purchase a SRF600 ADTR1.

Features

- External Thermistor Sensor Probe Range: -40°C to +125°C / -40°F to +257°F
- Selectable Scales °C/°F
- Battery Life: Up to 2 years
- Warranty: 1 Year
- LCD screen for local temperature measurement display
- LEDs indicate if alarms are active
- Selectable scales °C/°F
- Antimicrobial protection to impede development of bacteria, mold, and fungi as additional defense for high-risk environments
- Seamless connection to Setra's Continuous Environmental Monitoring Software (CEMS)


Technical Specs

Scales	°C and °F	
Internal Temp Range	Lithium Battery: -30 C to +60 C Alkaline Battery: -18 C to +55 C	
External Temp Range	-40 C to 125 C	
Resolution	0.1°C (0.2°F)	
Door Sensor Resolution	5 Seconds	
Instrument Accuracy	+/-0.1% ±0.2°C / ±0.4°F full range @ +23°C ambient	
System Accuracy (+23°C / +73°F)	+0°C to +70°C, +32°F to +158°F <±0.3°C / ±0.6°F *-25°C to 100°C, 13°F to +212°F ±0.5°C / ±0.9°F	
Temperature Coefficient	+/-0.005 degree/degree * When used with Setra probe	
Hi Hi / Lo Lo Alarm	Hi Hi and Lo Lo alarms with alarm delay and fully selectable alarms	
Alarm Delay	Delay is programmable for either Hi Hi or Lo Lo alarms or both independently 0-60 minutes	
Number of Internal Channels	1	
Number of External Channels	4	
Case Material	Rubber Over-Molding with BioCote® Antimicrobial	
Keypad	2 Button keypad standard on all models (Wi-Fi Provoke and Action Buttons)	
Battery Specifications	(Qty. 4) AA Alkaline Cells OR (Qty. 4) L91 Energizer Ultimate Lithium	
Battery Life	Up to 1 Year Battery Life with (Qty. 4) AA Alkaline Cells Up to 2 Years Battery Life with (Qty. 4) L91 Energizer Ultimate Lithium	
Wi-Fi	(IEEE 802.11b/g/n) WPA2 Pre-Shared Key	
Radio Range	Up to 15 meters indoors ESP-32	
Clock Accuracy	20ppm (1 minute/month) at 25°C (+77°F) Synchronized with the Cloud at least once per day	
Logging Memory	Channels	Total Records*
	1	140,000
	2	96,000
	3	76,000
	4	60,000
	5	52,000
	6	44,000
	*These numbers are absolute maximums and will be lower for multiple periods of data and/or when wraparound has been started.	
Logging Frequency	Programmable between 1 minute and 60 minutes	
Monitoring Frequency	1 Minute	
Radio Rate	5 minutes to 24 hours Battery life is stated for >=1 Hour Radio Rate	
Alarm / Active LEDs	GREEN LED flashing once per second indicates active logging RED LED flashing once per second indicates alarm Green LED indicates acknowledgement of long press of Wi-Fi button Green LED also indicates successful connection to the Cloud	
Status LEDs	Green LED indicates main power connected Red LED indicates Wi-Fi module is powered up Flashing Yellow LED indicates trying to connect to the Wi-Fi network Solid Yellow LED indicates Wi-Fi connected Solid Red/Yellow combined LED indicates the transmitter is connected to the Cloud and communicating	
Door Switch Alarms Continuous and Average	Continuous and average door alarms with 5 second detection period	
Audible Alarm Buzzer	Audible alarm buzzer can be deactivated in the task (Can be silenced with button press on the transmitter)	
Environmental Protection / Waterproof	IP65	
Dimensions	L 110mm x W 100mm x D 45mm	
Weight	300g	
Power Supply Unit (PSU)	Optional PSU Part No SRF600 PWR	
Maximum Probe Lead Length	Not to exceed 30m	
Warranty	1 Year	



Ordering Information

Example part number: SRF612



Compatible Probes and Accessories



Heavy Duty Door Event Sensor

The heavy-duty door event sensor can be used to trace changes in activity which lead to a rise or fall in temperatures beyond accepted limits.



PST Air Probe Duplex (2x2m Lead)

Temperature Range:
-40 to +70°C / -40°F to +158°F



6-Pin Lumberg Adapter

Allows you to connect up to four external 6-Pin Lumberg sensors to one wireless transmitter.



Mains Power Supply Unit

The Mains Power Supply Unit (PSU) serves as the power supply for SRF600 wireless transmitters when battery power is not acceptable or desired.



PST Air Probe (2.0m Lead)

Temperature Range:
-40 to +70°C / -40°F to +158°F



Standard Door Event Sensor

The Standard Door Event Sensor works with RF600 Wireless Transmitters to monitor activity on doors such as those on refrigerators and freezers.